
TFL VALVES

DZR BRASS BIB TAP (PLBRBP10)



DIMENSIONAL DRAWINGS



DIMENSIONS

ТҮРЕ	A	В	С
EBM-42-A		72	1/2"BSP
EBH-42-B	140	110	3/4"BSP
EBH-42-C	140	110	1"BSP

FEATURES & BENEFITS

- Bit tap with hose union.
- Screw Down T Handle.
- Hose tail outlet.
- Bronze/ DZR brass body.
- Fits directly into a wall socket.
- Locksheild type with spare key protect from unauthorisd operation.
- Bib tap with house union manufactured from DZR brass/bronze are suitable for use as an external supply, drain off tap, or standpipe.
- Available in Screw down T handle type.
 Designed to fix directly into a wall fitting, via the 1/2" or 3/4 or 1"
 male inlet. and terminates in a hose tail attached to the tap body.

MATERIAL SPECIFICATION

Part No.	Part Name	Material
1	BODY/CAP/PLUG/ADAPTOR	DZR BRASS/BRONZE
2	T HANDLE	BRASS
3	DISK	EPDM

PRESSURE / TEMPERATURE RATING

working Pressure	20 bar max.
working Temperature	90 °C max.

TEST PRESSURES


Shell	24 bar
Seat	17.6 bar

SPECIFICATION

• Inlet connection: 1/4" or 3/4" or 1" BSP male

• Outlet connection : Hose tail

PERFORMANCE



TFL Valves Quality Policy Is Complete Satisfaction Of Customers. According To That We Have Selected QUALITY As A Strategic factor in application to all our organization. Our purpose is to reinforce competitiveness, to ensure customer satisfaction, to improve process related with product quality and guarantee accomplishment of quality requirements.